



Pressure Switches

Miniature



Features:

- Patented shock and vibration resistance
- Miniature size, lightweight, low cost
- Quick response time
- Dependable long life (20+ million cycles)
- Gold contact points (dual)
- Rugged military standards (MIL-SPEC)



Dimensions : Inches (Millimetres)

Description:

The rugged yet ultra-sensitive PSF100A pressure switch incorporates a patented dual diaphragm/dual contact design offering protection against false actuation due to shock and vibration

Specifications:

Mechanical

Standard Tolerance	: ±20% (tighter tolerances available)
Switch Type	: SPST normally open, double-make / double-break
Switching Medium	: Air, compatible fluids on "High" side
Mechanical Life	: More than 20 million cycles

Pressure Switches



Miniature

- Proof Pressure : 8 psi : for units where set point is 3 inches H₂O or less
15 psi : for units where set point is greater than 3 inches H₂O
8 psi : for units with Teflon[®] diaphragm
- Shock and vibration : At zero pressure, will not make at 50 G's shock, will not make at 10 G's, 50 to 2,000 Hz vibration
- Operating Temperature : +40°F to +150°F (standard), -46°F to +205°F (contact us)

Physical

- Case Material : Polycarbonate (other materials available)
- Porting Options : Two 200 inches diameter barbed ports (low / high) for use with 1/8 inches to 3/16 inches ID tubing
- Diaphragm Material : Polyurethane (Teflon[®] optional)
- Contact Points : Gold (dual)
- Electrical Connections : Terminals - 0.187 inches × 0.02 inches tab-type, for use with quick disconnects (reference AMP 2-520182-2 or equivalent)
- Mounting : Eyeleted for #2 screws; mounting clip or bracket available
- Weight : Less than 10 g

Electrical

- Current Rating : 40 mA resistive for life in excess of 20 million cycles
- Operating Voltage : 30 V ac / dc or less with resistive load; 120 V ac neon lamp load

Note : For high load capabilities contact design flex for our SRF solid state relay

Specification Table

Description	Inches H ₂ O	mbar	psi	Part Number
Pressure switch, 0.004 - 0.018 psi	0.1 to 0.5	0.25 to 1.25	0.004 to 0.018	PSF100A-0.5
Pressure switch, 0.054 psi	1.5	3.73	0.054	PSF100A-1.5
Pressure switch, 0.108 psi	3	7.46	0.108	PSF100A-3.0
Pressure switch, 0.217 psi	6	14.92	0.217	PSF100A-6.0
Pressure switch, 0.361 psi	10	24.86	0.361	PSF100A-10.0
Pressure switch, 0.541 psi	15	37.3	0.541	PSF100A-15.0
Pressure switch, 1.804 psi	50	124.32	1.804	PSF100A-50.0

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.